

AMENDMENTS TO THE CLAIMS

No claims are canceled.

No claims are added.

5 No claims are amendeded.

Accordingly, claims 1-15 remain pending.

1. (Previously Presented) A computer-readable medium having
computer-executable instructions for operating a policy agent of a network for
10 performing steps comprising:

detecting a network connection from a client computer on the network;

composing a challenge for authenticating a user of the client computer
associated with said network connection, the challenge being encrypted with a
private key of the policy agent;

15 transmitting the challenge to the client computer;

receiving a response from the client computer;

decrypting the response using a public key of the user to obtain a first
message digest value;

20 receiving network data through the network connection with the client
computer;

calculating a second message digest value based on the challenge and
the received network data;

comparing the first and second message digest values to determine
whether a match is found; and

if a match is found, then forwarding the network data to their specified recipient, else not forwarding the network data to their specified recipient.

2. (Original) A computer-readable medium as in claim 1, wherein
5 the policy agent is a firewall.

3. (Previously Presented) A computer-readable medium as in
claim 1, wherein the step of composing includes encrypting the challenge with a
public key of the user.

10

4. (Original) A computer-readable medium as in claim 3, wherein
the step of decrypting includes decrypting the response with a private key of the
policy agent.

15 5. (Original) A computer-readable medium as in claim 1, wherein
the step of composing includes generating a third digest value from data
including a time value, and encrypting the third digest value with the private key
of the policy agent.

20 6. (Original) A computer-readable medium as in claim 1, wherein
the received network data are in a form of packets, and the step of calculating
calculates the second message digest value based on a pre-selected number of
packets of the received network data.

7. (Original) A computer-readable medium as in claim 1, having further computer-executable instructions for performing network access policies on the received network data according to the identify of the user after a match between the first and second message digest values is found.

5

8. (Previously Presented) A method of authenticating a user using a client computer on a network to transmit network data through a policy agent of the network, comprising the steps of:

detecting by the policy agent a network connection from the client
10 computer for transmitting network data of the user;

receiving by the policy agent network data transmitted through the network connection from the client computer;

obtaining, by the policy agent, an identity of the user and a public key of the user;

15 composing, by the policy agent, a challenge encrypted with a private key of the policy agent;

sending the challenge to the client computer;

decrypting, by the client computer, the challenge;

generating, by the client computer, a first message digest value based
20 on the challenge and the network data of the user;

encrypting, by the client computer, the first message digest value with a private key of the user to create a response;

sending the response to the policy agent;

decrypting, by the policy agent, the response to obtain the first message digest value;

calculating, by the policy agent, a second message digest value based on the challenge and the network data received through the network connection
5 from the client computer;

comparing the first and second message digest values to determine whether there is a match therebetween, and

if a match is found, then forwarding, by the policy agent, the network data to their specified recipient, else not forwarding the network data to their
10 specified recipient.

9. (Original) A method as in claim 8, further including the step of applying network policies by the policy agent on the received network data based on the identity of the user after a match between the first and second
15 message digest values is found.

10. (Original) A method as in claim 8, wherein the step of composing the challenge includes encrypting the challenge with the public key of the user.

20 11. (Original) A method as recited in claim 8, wherein the step of encrypting by the client computer includes encrypting the first message digest value with a public key of the policy agent.

12. (Previously Presented) A method as in claim 8, wherein the step of composing the challenge includes generating a third message digest value based on data including a time value and encrypting the third message digest value to form the challenge.

5

13. (Original) A method as in claim 8, wherein the received network data are in a form of packets, and the step of generating by the client computer generates the first message digest value based on data of a pre-selected number of packets of the received network data.

10

14. (Original) A method as in claim 8, wherein the step of generating by the client computer generates the first message digest value based on a random number, data decrypted from the challenge, and data of the pre-selected packets of the received network data.

15

15. (Original) A method as in claim 8, wherein the policy agent is a firewall of the network.

20